



SIMATIC S7-1200, Digital output SM 1222, 16 DO, 24 V DC, sourcing (Sinking Output), NPN transistor 0.5 A

General information	
Product type designation	SM 1222, DO 16x 24 V DC/0.5 A Sink
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	140 mA
Power loss	
Power loss, typ.	2.5 W
Digital outputs	
Number of digital outputs	16
• in groups of	1
Current-sinking	Yes
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	Typ 45 V
Switching capacity of the outputs	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
Output voltage	
• Rated value (DC)	24 V
• for signal "0", max.	L+ minus 0.75 V DC with 10k Load
• for signal "1", min.	0.5 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	75 µA
Output delay with resistive load	
• "0" to "1", max.	20 µs
• "1" to "0", max.	350 µs
Total current of the outputs (per group)	
horizontal installation	
— up to 50 °C, max.	8 A; Current per mass
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
Diagnostics indication LED	
• for status of the outputs	Yes
Potential separation	

Potential separation digital outputs			
• between the channels, in groups of • between the channels and backplane bus	1 500 V AC		
Degree and class of protection			
IP degree of protection	IP20		
Standards, approvals, certificates			
CE mark	Yes		
CSA approval	Yes		
UL approval	Yes		
cULus	Yes		
FM approval	Yes		
RCM (formerly C-TICK)	Yes		
KC approval	Yes		
Marine approval	Yes		
Ambient conditions			
Ambient temperature during operation			
• min. • max. • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. • permissible temperature change	-20 °C 60 °C -20 °C 60 °C -20 °C 50 °C 5°C to 55°C, 3°C / minute		
Ambient temperature during storage/transportation			
• min. • max.	-40 °C 70 °C		
Air pressure acc. to IEC 60068-2-13			
• Storage/transport, min. • Storage/transport, max.	660 hPa 1 080 hPa		
Relative humidity			
• Operation at 25 °C without condensation, max.	95 %		
connection method			
required front connector	Yes		
Mechanics/material			
Enclosure material (front)			
• Plastic	Yes		
Dimensions			
Width	45 mm		
Height	100 mm		
Depth	75 mm		
Weights			
Weight, approx.	220 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-04
	eClass	12	27-24-22-04
	eClass	9.1	27-24-22-04
	eClass	9	27-24-22-04
	eClass	8	27-24-22-04
	eClass	7.1	27-24-22-04
	eClass	6	27-24-22-04
	ETIM	10	EC001419
	ETIM	9	EC001419
	ETIM	8	EC001419
	ETIM	7	EC001419
	IDEA	4	3566
	UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------

[Manufacturer Declaration](#)

[Miscellaneous](#)


RCM


RCM


IECEX

[FM](#)

For use in hazardous locations	Maritime application
--------------------------------	----------------------


UL


UL

[CCC-Ex](#)


DNV


RMRS

last modified:

7/2/2025 